

MATERIAL SAFETY DATA SHEET

ACE LACQUER THINNER

HEALTH		2	
FLAMMABILITY		3	
PHYSICAL HAZ.		0	
PPE	G		



Printed: 03/24/2009

Revision: 07/08/2008

Date Created: 07/08/2008

1. Product and Company Identification

Product Code: 1605.03D
Product Name: ACE LACQUER THINNER
Reference #: 1605.03D
Manufacturer Information
Company Name: W. M. Barr
 2105 Channel Avenue
 Memphis, TN 38113
Phone Number: (901)775-0100
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Web site address: www.wmbarr.com
Preparer Name: W.M. Barr EHS Dept (901)775-0100
Synonyms
 GA12784, PA12782, QA12783

2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA TWA	ACGIH TWA	Other Limits
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	10.0 -40.0 %	200 ppm	200 ppm	No data.
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	5.0 -20.0 %	200 ppm	50 ppm	No data.
3. Acetone	67-64-1	5.0 -20.0 %	1000 ppm	500 ppm	No data.
4. Hexane, Light aliphatic naptha {Light aliphatic solvent naphtha (petroleum)}	64742-89-8	25.0 -50.0 %	500 ppm	400 ppm	No data.
5. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	5.0 -15.0 %	200 ppm	200 ppm	No data.
6. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	1.0 -5.0 %	400 ppm	400 ppm	No data.
7. Propylene glycol methyl ether acetate {(not 313)}	108-65-6	1.0 -5.0 %	No data.	No data.	No data.
8. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	1.0 -5.0 %	No data.	100 ppm	No data.
9. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	1.0 -5.0 %	No data.	100 ppm	No data.
10. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	1.0 -5.0 %	No data.	100 ppm	No data.
Hazardous Components (Chemical Name)	CAS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	No data.	No data.	250 ppm	No data.
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	500 ppm/(10min)	300 ppm	No data.	No data.
3. Acetone	67-64-1	No data.	No data.	750 ppm	No data.
4. Hexane, Light aliphatic naptha {Light aliphatic solvent naphtha (petroleum)}	64742-89-8	No data.	No data.	No data.	No data.
5. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	No data.	No data.	300 ppm	No data.
6. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	No data.	No data.	No data.	No data.
7. Propylene glycol methyl ether acetate {(not 313)}	108-65-6	No data.	No data.	No data.	No data.
8. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	No data.	No data.	150 ppm	No data.
9. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	No data.	No data.	150 ppm	No data.
10. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	No data.	No data.	150 ppm	No data.

3. Hazards Identification

Emergency Overview

Danger! Extremely flammable. Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause flash fire or ignite explosively. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by clothing and other sources.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness; headache; watering of eyes; irritation of respiratory tract; weakness; drowsiness; nausea; numbness in fingers, arms and legs; depression of central nervous system; loss of appetite; fatigue; hallucinations; light headedness; visual disturbances; giddiness and intoxication; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; vomiting; dilation of pupils; spotted vision. Severe overexposure may cause convulsions; unconsciousness; coma; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May be absorbed through the skin. May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

Ingestion Acute Exposure Effects:

Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May cause dizziness; headache; nausea; vomiting; burning sensation in mouth, throat, and stomach; loss of coordination; depression of the central nervous system; narcosis; stupor; gastrointestinal irritation; liver, kidney, and heart damage; diarrhea; loss of appetite; coma and death. May produce symptoms listed under inhalation.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause conjunctivitis; gastric disturbances; insomnia; dizziness; headache; weakness; fatigue; nausea; heart palpitations; skin irritation; numbness in hands and feet; permanent central nervous system changes; some loss of memory; pancreatic damage; giddiness; visual impairment or blindness; kidney or liver damage; and death. May cause symptoms listed under inhalation.

Signs and Symptoms Of Exposure

No data available.

Medical Conditions Generally Aggravated By Exposure

Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

Skin Contact:

MATERIAL SAFETY DATA SHEET

ACE LACQUER THINNER

Page: 3
Printed: 03/24/2009
Revision: 07/08/2008

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:

Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

Note to Physician

Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further information.

5. Fire Fighting Measures

Flammability Classification:

Class IB

Flash Pt:

< 20.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits:

LEL: No data.

UEL: No data.

Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards

No data available.

Hazardous Combustion Products

Carbon monoxide and carbon dioxide.

Extinguishing Media

Use carbon dioxide, dry powder, or foam.

Unsuitable Extinguishing Media

No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Clean up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small spills:

Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

MATERIAL SAFETY DATA SHEET

ACE LACQUER THINNER

Page: 4
Printed: 03/24/2009
Revision: 07/08/2008

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. Exposure Controls/Personal Protection

Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection

Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

9. Physical and Chemical Properties

Physical States:	[] Gas	[X] Liquid	[] Solid
Melting Point:	No data.		
Boiling Point:	133.00 F		
Autoignition Pt:	No data.		
Flash Pt:	< 20.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)		
Explosive Limits:	LEL: No data.		UEL: No data.
Specific Gravity (Water = 1):	0.762 - 0.78		
Bulk density:	No data.		
Vapor Pressure (vs. Air or mm Hg):	59 MM HG		
Vapor Density (vs. Air = 1):	> 1		
Evaporation Rate (vs Butyl Acetate=1):	No data.		

MATERIAL SAFETY DATA SHEET
ACE LACQUER THINNER

Page: 5
Printed: 03/24/2009
Revision: 07/08/2008

Solubility in Water: No data.
Solubility Notes
Partially soluble in water.
Percent Volatile: 100.0 % by weight.
VOC / Volume: 689.0000 G/L
Heat Value: No data.
Particle Size: No data.
Corrosion Rate: No data.
pH: No data.
Appearance and Odor
Water White / Free and Clear

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

Incompatible with strong oxidizing agents, strong caustics, hydrogen peroxide, and nitrates.

Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide; carbon dioxide; formaldehyde; and unidentified organic compounds in black smoke.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Polymerization

No data available.

11. Toxicological Information

No data available.

Carcinogenicity/Other Information

No data available.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	n.a.	n.a.	n.a.	n.a.
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	No	3	A4	No
3. Acetone	67-64-1	n.a.	n.a.	A4	n.a.
4. Hexane, Light aliphatic naptha {Light aliphatic solvent naphtha (petroleum)}	64742-89-8	n.a.	n.a.	n.a.	n.a.
5. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	n.a.	n.a.	n.a.	n.a.
6. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	n.a.	n.a.	n.a.	n.a.
7. Propylene glycol methyl ether acetate {(not 313)}	108-65-6	n.a.	n.a.	n.a.	n.a.
8. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	n.a.	n.a.	A4	n.a.
9. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	n.a.	n.a.	A4	n.a.
10. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	n.a.	n.a.	A4	n.a.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

No data available.

MATERIAL SAFETY DATA SHEET

ACE LACQUER THINNER

Page: 6
Printed: 03/24/2009
Revision: 07/08/2008

13. Disposal Considerations

Waste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations.

14. Transport Information

LAND TRANSPORT (US DOT)

<p>DOT Proper Shipping Name</p> <p>DOT Hazard Class:</p> <p>DOT Hazard Label:</p> <p>UN/NA Number:</p> <p>Packing Group:</p>	<p>Paint Related Material</p> <p>3</p> <p>FLAMMABLE LIQUID</p> <p>UN1263</p> <p>II</p>
---	--

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	No	Yes 5000 LB	Yes	No
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	No	Yes 1000 LB	Yes	Yes
3. Acetone	67-64-1	No	Yes 5000 LB	No	Yes
4. Hexane, Light aliphatic naptha {Light aliphatic solvent naphtha (petroleum)}	64742-89-8	No	No	No	
5. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	No	Yes 5000 LB	No	Yes
6. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	No	Yes 5000 LB	No	No
7. Propylene glycol methyl ether acetate {(not 313)}	108-65-6	No	No	Yes-Cat. N230	
8. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	No	Yes 1000 LB	Yes	No
9. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	No	Yes 100 LB	Yes	Yes
10. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	No	Yes 1000 LB	Yes	Yes

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Methanol {Methyl alcohol; Carbinol; Wood alcohol}	67-56-1	HAP		Inventory	
2. Toluene {Benzene, Methyl-; Toluol}	108-88-3	HAP	Yes	Inventory, 8A CAIR, 8A PAIR	Yes
3. Acetone	67-64-1	No		Inventory, 4 Test, 12(b)	
4. Hexane, Light aliphatic naptha {Light aliphatic solvent naphtha (petroleum)}	64742-89-8	No		Inventory	
5. Methyl ethyl ketone {MEK; 2-Butanone}	78-93-3	HAP		Inventory, 8A PAIR	
6. Acetic acid, Ethyl ester {Ethyl acetate}	141-78-6	No		Inventory, 4 Test, 8A PAIR, 12(b)	
7. Propylene glycol methyl ether acetate {(not 313)}	108-65-6	No		Inventory, 8A PAIR, 8D TERM	
8. m-Xylene {Benzene, m-Dimethyl-}	108-38-3	HAP		Inventory, 8A PAIR	
9. p-Xylene {Benzene, p-Dimethyl-}	106-42-3	HAP		Inventory, 8A PAIR, 8D	
10. o-Xylene {Benzene, o-Dimethyl-}	95-47-6	HAP		Inventory, 8A PAIR	

SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

Sec.302: EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.

Sec.304: EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.

MATERIAL SAFETY DATA SHEET

ACE LACQUER THINNER

Page: 7
Printed: 03/24/2009
Revision: 07/08/2008

Sec.313: EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.

Sec.110: EPA SARA 110 Superfund Site Priority Contaminant List

TSCA (Toxic Substances Control Act) Lists:

Inventory: Chemical Listed in the TSCA Inventory.
5A(2): Chemical Subject to Significant New Rules (SNURS)
6A: Commercial Chemical Control Rules
8A: Toxic Substances Subject To Information Rules on Production
8A CAIR: Comprehensive Assessment Information Rules - (CAIR)
8A PAIR: Preliminary Assessment Information Rules - (PAIR)
8C: Records of Allegations of Significant Adverse Reactions
8D: Health and Safety Data Reporting Rules
8D TERM: Health and Safety Data Reporting Rule Terminations
12(b): Notice of Export

Other Important Lists:

CWA NPDES: EPA Clean Water Act NPDES Permit Chemical
CAA HAP: EPA Clean Air Act Hazardous Air Pollutant
CAA ODC: EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
CA PROP 65: California Proposition 65

International Regulatory Lists:

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

Yes No Acute (immediate) Health Hazard
 Yes No Chronic (delayed) Health Hazard
 Yes No Fire Hazard
 Yes No Sudden Release of Pressure Hazard
 Yes No Reactive Hazard

16. Other Information

Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.