



Revision Number: 005.0

Issue date: 08/30/2017

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE LB 8151 AE known as LOCTITE® SILVER GRADE ANTI-SEI</b>	<b>IDH number:</b>	135541
<b>Product type:</b>	Lubricant	<b>Item number:</b>	76759
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** CONTENTS UNDER PRESSURE.  
EXTREMELY FLAMMABLE AEROSOL.  
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.  
MAY CAUSE DROWSINESS OR DIZZINESS.  
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
SKIN CORROSION	1C
SERIOUS EYE DAMAGE	1
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust or fumes. Avoid breathing mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

**Response:**

IF SWALLOWED: Immediately call a physician or poison control center. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Wash contaminated clothing before reuse.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal:**

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Acetone	67-64-1	10 - 20
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	93924-37-9	10 - 20
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 20
Graphite	7782-42-5	5 - 10
Propane	74-98-6	5 - 10
Butane	106-97-8	5 - 10
Calcium oxide	1305-78-8	5 - 10
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	5 - 10
Aluminum not powder, dust or fume	7429-90-5	1 - 5
Cyclohexane	110-82-7	1 - 5
Distillates (petroleum), straight-run middle	64741-44-2	1 - 5
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - 1
n-Hexane	110-54-3	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Remove contaminated clothing and footwear. Wash with soap and water. If symptoms develop and persist, get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
<b>Unusual fire or explosion hazards:</b>	Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture or incinerate pressurized containers. Exposure to temperatures above 49°C (120°F) may cause container to burst.
<b>Hazardous combustion products:</b>	Oxides of carbon. Toxic and irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Remove all sources of ignition. Ensure adequate ventilation. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Vapors will accumulate readily and may ignite explosively. Refer to Section 8.
<b>Storage:</b>	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F).

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m <sup>3</sup> ) PEL	None	None
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	None	None	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m <sup>3</sup> TWA Inhalable fraction. 5 mg/m <sup>3</sup> TWA mist 10 mg/m <sup>3</sup> STEL mist	5 mg/m <sup>3</sup> TWA mist 500 ppm (2,000 mg/m <sup>3</sup> ) PEL 5 mg/m <sup>3</sup> PEL Mist.	None	None
Graphite	2 mg/m <sup>3</sup> TWA Respirable fraction.	5 mg/m <sup>3</sup> PEL Respirable fraction. 15 mg/m <sup>3</sup> PEL Total dust. 15 MPPCF TWA	None	None
Propane	Included in the regulation but with no data values. See regulation for further details (Simple asphyxiant.)	1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None
Butane	1,000 ppm STEL	None	None	None
Calcium oxide	2 mg/m <sup>3</sup> TWA	5 mg/m <sup>3</sup> PEL	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m <sup>3</sup> TWA Inhalable fraction.	5 mg/m <sup>3</sup> PEL Mist. 500 ppm (2,000 mg/m <sup>3</sup> ) PEL	None	None
Aluminum not powder, dust or fume	None	5 mg/m <sup>3</sup> PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m <sup>3</sup> TWA Respirable fraction. 15 mg/m <sup>3</sup> TWA Total dust.	None	None
Cyclohexane	100 ppm TWA	300 ppm (1,050 mg/m <sup>3</sup> ) PEL	None	None
Distillates (petroleum), straight-run middle	5 mg/m <sup>3</sup> TWA mist 10 mg/m <sup>3</sup> STEL mist	5 mg/m <sup>3</sup> TWA mist	None	None
Quartz (SiO <sub>2</sub> )	0.025 mg/m <sup>3</sup> TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m <sup>3</sup> TWA Respirable. 0.05 mg/m <sup>3</sup> TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m <sup>3</sup> OSHA ACT (Respirable dust.) 0.05 mg/m <sup>3</sup> PEL Respirable dust.	None	None
n-Hexane	50 ppm TWA (SKIN)	500 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Aerosol, liquid
<b>Color:</b>	Silver
<b>Odor:</b>	Mild, Petroleum
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	0 - 212 °F (-17.8 - 100°C)
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.77
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	< -18 °C (< 0.4 °F) ; (value for propellant).
<b>Flame projection:</b>	122.00 cm (48.03 inch)
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Extremely flammable aerosol.
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not available.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	42 %; 323 g/l
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Irritating organic vapours. Oxides of carbon.
<b>Incompatible materials:</b>	Oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Keep away from heat, spark and flame. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F).

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects/Symptoms**

**Inhalation:** May cause respiratory tract irritation. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness. Extreme overexposure may result in unconsciousness and possibly death. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

**Skin contact:** Causes skin burns.

**Eye contact:** Causes serious eye damage. Direct spray or vapors will irritate and may harm eyes.

**Ingestion:** This product may be fatal if it is swallowed. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l	Central nervous system, Irritant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	None	No Data
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Graphite	None	Lung
Propane	None	Cardiac, Central nervous system, Irritant
Butane	Inhalation LC50 (Rat, 4 h) = 658 mg/l	Cardiac, Central nervous system, Irritant
Calcium oxide	None	Irritant, Corrosive, Eyes
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
Aluminum not powder, dust or fume	None	Central nervous system, Irritant, Lung
Cyclohexane	Oral LD50 (Rat) = 29,820 mg/kg Oral LD50 (Mouse) = 1,300 mg/kg	Irritant, Central nervous system
Distillates (petroleum), straight-run middle	None	Irritant
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity
n-Hexane	Oral LD50 (Rat) = 28,710 mg/kg Dermal LD50 (Rabbit) = > 2,000 mg/kg Inhalation LC50 (Rat, 4 h) = 73860 ppm Inhalation LC50 (Mouse, 4 h) = 48000 ppm	Developmental, Irritant, Lung, Nervous System, Reproductive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Graphite	No	No	No
Propane	No	No	No
Butane	No	No	No
Calcium oxide	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Aluminum not powder, dust or fume	No	No	No
Cyclohexane	No	No	No
Distillates (petroleum), straight-run middle	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes
n-Hexane	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable. This product may contain traces of: D018: Benzene (Check TCLP Level).

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Cyclohexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None  
Marine pollutant: Cyclohexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.

**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire, Pressure

**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cyclohexane (CAS# 110-82-7).

**CERCLA Reportable quantity:** Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)  
Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)  
Butane (CAS# 106-97-8) 100 lbs. (45.4 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 08/30/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.