

Safety Data Sheet ABUDAWOOD, TEL-X PLUS AEROSOL, DZ, NAC MM

Supersedes Date Not applicable

Issuing Date 01/28/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ABUDAWOOD, TEL-X PLUS AEROSOL, DZ, NAC MM
Recommended use Lubricant
Information on Manufacturer
CHEMSEARCH DIV. OF NCH CORP.
BOX 152170
IRVING, TX 75015

Product Code 5436
Chemical nature Resins in solution
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color White

Physical state liquid

Odor Petroleum

GHS

Classification

Physical Hazards

Flammable Aerosols
Gases under pressure

Category 1
Liquefied gas

Health Hazard

Aspiration Toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ systemic toxicity (single exposure)

Category 1
Category 2
Category 2A
Category 3

Other hazards

None

Labeling

Signal Word

DANGER



Hazard statements

H222 - Extremely flammable aerosol
H336 - May cause drowsiness or dizziness
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H304 - May be fatal if swallowed and enters airways
H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe vapor, mist or gas
P271 - Use in a well-ventilated area.
P280 - Wear protective gloves, protective clothing and eye protection.
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product.
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a physician if unwell.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P332 + P313 - If skin irritation occurs, get medical attention.
P362 - Take off contaminated clothing and wash before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists, get medical attention.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P403 + P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents and container in accordance with applicable local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight % *
Petroleum gases, liquified, sweetened	68476-86-8	30-60
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	64741-66-8	15-40
Heptane (n-)	142-82-5	10-30
Isopropyl alcohol	67-63-0	7-13

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur. Never give anything by mouth to an unconscious person.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point	No data available	Method	Seta closed cup
Flammability Limits in Air %: Mixture.		Upper:	12.7
Suitable Extinguishing Media		Lower:	1.05
Foam. Dry chemical. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Unsuitable Extinguishing Media	Water spray/stream.		
Specific hazards arising from the chemical	Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: 30 inches / 75 cm and Burnback: 0 inch / 0 cm. Extremely flammable. Material can create slippery conditions.		
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) -	3		
NFPA	Health 2	Flammability 4	Instability 0
HMIS	Health 2	Flammability 4	Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Take precautionary measures against static discharges. Remove all sources of ignition. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.			
Storage	Keep away from heat and sources of ignition.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH

Heptane (n-)	TWA: 400 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 2000 mg/m ³	750 ppm Ceiling: 440 ppm Ceiling: 1800 mg/m ³ TWA: 85 ppm TWA: 350 mg/m ³
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³	2000 ppm STEL 500 ppm STEL 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin Protection

For prolonged or repeated contact, use protective gloves with appropriate chemical resistance.

Respiratory Protection

In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid	Viscosity	Non viscous
Color	White	Odor	Petroleum
Odor Threshold	Not applicable	Appearance	Hazy
pH	Not applicable	Specific Gravity	0.725
Evaporation Rate	>2.5 (Butyl acetate=1)	Percent Volatile (Volume)	99
VOC Content (%)	98.2	VOC Photoreactive (Y/N)	Yes
VOC Content (g/L)	738	Vapor Pressure	124 mm Hg
Vapor Density	> 2 (Air = 1.0)	Solubility	Insoluble
n-Octanol/Water Partition	No data available	Melting Point/Range	No data available
Decomposition Temperature	No data available	Boiling Point/Range	No data available
Flammability (solid, gas)	No data available	Method	Seta closed cup
Flash Point	No data available		
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Mixture	Upper: 12.7 Lower: 1.05	

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition.
Incompatible Products	Strong oxidizing agents.
Decomposition Temperature	No data available
Hazardous Decomposition Products	Carbon oxides.
Possibility of Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Dermal LD50 No information available

Inhalation LC50

Gas No information available

Mist No information available

Vapor No information available

Principle Route of Exposure Inhalation, Skin contact, Eye contact.

Primary Routes of Entry Skin contact, Eye contact, Ingestion, Inhalation.

Acute Effects:

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

Inhalation May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. May be fatal if inhaled in large quantities.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity No information available.

Target Organ Effects Eyes, Skin, Respiratory system, Central nervous system.

Aggravated Medical Conditions Skin disorders, Respiratory disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Naphtha (petroleum)light alkylate (<3% DMSO extractable) 64741-66-8	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h	no data available	no data available
Heptane (n-) 142-82-5	no data available	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h	no data available	no data available
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Heptane (n-) 142-82-5	no data available	no data available	no data available	no data available	Skin Central nervous system Respiratory system
Isopropyl alcohol 67-63-0	no data available	no data available	no data available	no data available	Skin Eyes Respiratory system

Carcinogenicity There are no known carcinogenic chemicals in this product.**12. ECOLOGICAL INFORMATION**

Product Information No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
Petroleum gases, liquified, sweetened	No information available.	No information available.	No information available	No information available.	2.8
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	EC50 = 30000 mg/L Pseudokirchneriella subcapitata 72 h	No information available.	No information available	2: 48 h Mysidopsis bahia mg/L LC50	N/A
Heptane (n-)	No information available.	LC50 = 375.0 mg/L Cichlid fish 96 h	No information available	No information available.	4.66
Isopropyl alcohol	EC50 > 1000 mg/L Desmodesmus subspicatus 96 h EC50 > 1000 mg/L Desmodesmus subspicatus 72 h	LC50 = 9640 mg/L Pimephales promelas 96 h LC50 = 11130 mg/L Pimephales promelas 96 h LC50 > 1400000 µg/L Lepomis macrochirus 96 h	EC50 = 35390 mg/L 5 min	13299: 48 h Daphnia magna mg/L EC50	0.05

Persistence and Degradability

Not readily biodegradable.

Bioaccumulation

Not likely to bioaccumulate.

Mobility

This product is mobile in soil.

13. DISPOSAL CONSIDERATIONS**Product Disposal**

Dispose of in accordance with local regulations.

Container Disposal

Contents under pressure. Do not puncture. Empty containers should be taken for local recycling, recovery, or waste disposal. Empty remaining contents.

14. TRANSPORT INFORMATION**DOT**

Proper Shipping Name Consumer commodity
Hazard Class ORM-D
Description Consumer commodity ,ORM-D,

TDG

Proper shipping name Aerosols
Hazard Class 2.1
UN-No UN1950
Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO

UN-No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Shipping Description Aerosols,UN1950 LTD. QTY.

IATA

UN-No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
ERG-Code 10L
Shipping Description UN1950,Aerosols, flammable,2.1 LTD. QTY.

IMDG/IMO

Proper Shipping Name Aerosols
Hazard Class 2.1
UN-No UN1950
EmS No. F-D, S-U
Description UN1950, Aerosols,2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	No	Yes	Yes	No

CERCLA

16. OTHER INFORMATION

Prepared By Samantha Purvis
Supersedes Date Not applicable
Issuing Date 01/28/2016
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.