

Material Safety Data Sheet



Date of issue 10 March 2014

Version 11

1. Product and company identification

Product name : Delstar Acrylic Enamel
Code : DAR-1
Supplier : PPG Industries, Inc.
One PPG Place,
Pittsburgh, PA 15272
Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
Technical Phone Number : (740) 363-9610 (DELAWARE, OH) 8:00 a.m. - 5:00 p.m. EST

2. Hazards identification

Emergency overview : DANGER!
 FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED. SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED. ASPIRATION HAZARD. CAN ENTER LUNGS AND CAUSE DAMAGE. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
 Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Keep away from heat. Do not smoke. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation : May be harmful if inhaled. Severely irritating to the respiratory system. Can irritate eyes, nose, mouth and throat. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion : May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.
Skin : Harmful in contact with skin. Irritating to skin. May cause an allergic skin reaction.
Eyes : Irritating to eyes.

Over-exposure signs/symptoms

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. 1-component mixtures: formaldehyde is released during curing. Formaldehyde may cause irreversible effects, is irritating to the mucous membranes and may cause skin sensitization. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications.

Medical conditions aggravated by over-exposure : Pre-existing skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

2. Hazards identification

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
xylene	1330-20-7	60 - 100
diiron trioxide	1309-37-1	60 - 100
titanium dioxide	13463-67-7	40 - 70
Mica-group minerals	12001-26-2	40 - 70
ethylbenzene	100-41-4	15 - 40
n-butyl acetate	123-86-4	15 - 40
Naphtha (petroleum), heavy alkylate	64741-65-7	10 - 30
heptan-2-one	110-43-0	10 - 30
Talc , not containing asbestiform fibres	14807-96-6	7 - 13
Aluminium powder (stabilized)	7429-90-5	7 - 13
butanone	78-93-3	5 - 10
ammonium iron(3+) hexakis(cyano-C)ferrate(4-)	25869-00-5	5 - 10
toluene	108-88-3	5 - 10
Silica gel, pptd., cryst.-free	112926-00-8	5 - 10
2-methoxy-1-methylethyl acetate	108-65-6	5 - 10
zirconium dioxide	1314-23-4	1 - 5
tin dioxide	18282-10-5	1 - 5
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	1 - 5
Stoddard solvent	8052-41-3	1 - 5
Isopropyl alcohol	67-63-0	1 - 5
Solvent naphtha (petroleum), light aromatic	64742-95-6	1 - 5
polychloro copper phthalocyanine	1328-53-6	1 - 5
copper chlorophthalocyanine	12239-87-1	1 - 5
[1,3,8,16,18,24-hexabromo-2,4,9,10,11,15,17,22,23,25-decachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]copper	14302-13-7	1 - 5
carbon black respirable	1333-86-4	1 - 5
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	1 - 5
Resin acids and Rosin acids, calcium salts	9007-13-0	0.5 - 1.5
quino[2,3-b]acridine-6,7,13,14(5H,12H)-tetrone	1503-48-6	0.5 - 1.5
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0.5 - 1.5
aluminium hydroxide	21645-51-2	0.5 - 1.5
benzyl butyl phthalate	85-68-7	0.1 - 1
2-butanone oxime	96-29-7	0.1 - 1
crystalline silica respirable (<10 microns)	14808-60-7	0.1 - 1
2-ethylhexanoic acid	149-57-5	0.1 - 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

4 . First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.


5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
sulfur oxides
halogenated compounds
metal oxide/oxides
Formaldehyde.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures


- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Use spark-proof tools and explosion-proof equipment. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling :  Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Vapors are heavier than air and may spread along floors. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120F / 49C.

8. Exposure controls/personal protection

Name	Result	ACGIH	OSHA	Ontario	Mexico	PPG
 xylene	TWA	100 ppm	100 ppm	100 ppm	100 ppm	Not established
	STEL	150 ppm	Not established	150 ppm	150 ppm	Not established
diiron trioxide	TWA	5 mg/m ³ R	10 mg/m ³	5 mg/m ³ R	5 mg/m ³ (as Fe)	Not established
	STEL	Not established	Not established	Not established	10 mg/m ³ (as Fe)	Not established
titanium dioxide	TWA	10 mg/m ³	15 mg/m ³ TD	10 mg/m ³ TD	10 mg/m ³ (as Ti)	Not established
	STEL	Not established	Not established	Not established	20 mg/m ³ (as Ti)	Not established
Mica-group minerals	TWA	3 mg/m ³ R	20 mppcf Z	3 mg/m ³ R	3 mg/m ³	Not established
ethylbenzene	TWA	20 ppm	100 ppm	20 ppm	100 ppm	Not established
	STEL	Not established	Not established	Not established	125 ppm	Not established

Product name Delstar Acrylic Enamel

8 . Exposure controls/personal protection

n-butyl acetate	TWA	150 ppm	150 ppm	150 ppm	150 ppm	Not established
	STEL	200 ppm	Not established	200 ppm	200 ppm	Not established
heptan-2-one	TWA	50 ppm	100 ppm	25 ppm	50 ppm	Not established
	STEL	Not established	Not established	Not established	100 ppm	Not established
Talc , not containing asbestiform fibres	TWA	Not established	20 mppcf Z	2 mg/m ³ R 2 f/cc	2 mg/m ³ R 6 mg/m ³ 3 mg/m ³ R	Not established
Aluminium powder (stabilized)	TWA	1 mg/m ³ R	15 mg/m ³ (as Al) TD 5 mg/m ³ (as Al) R	1 mg/m ³ R	5 mg/m ³ 5 mg/m ³	Not established
butanone	TWA	200 ppm	200 ppm	200 ppm	200 ppm	Not established
	STEL	300 ppm	Not established	300 ppm	300 ppm	Not established
ammonium iron(3+) hexakis (cyano-C)ferrate(4-)	TWA	1 mg/m ³ (as Fe)	5 mg/m ³ (as CN) S	1 mg/m ³ (as Fe)	1 mg/m ³ (as Fe) 5 mg/m ³ (as Cn)	Not established
	STEL	5 mg/m ³ S C	Not established	Not established	2 mg/m ³ (as Fe)	Not established
toluene	TWA	20 ppm	200 ppm Z	20 ppm	50 ppm S	Not established
	STEL	Not established	500 ppm Z A 300 ppm Z C	Not established	Not established	Not established
Silica gel, pptd., cryst.-free	TWA	Not established	Not established	10 mg/m ³	10 mg/m ³	Not established
2-methoxy-1-methylethyl acetate	TWA	Not established	Not established	50 ppm	Not established	50 ppm
zirconium dioxide	TWA	5 mg/m ³ (as Zr)	5 mg/m ³ (as Zr) 5 mg/m ³ (as Zr)	5 mg/m ³ (as Zr)	5 mg/m ³ (as Zr)	Not established
	STEL	10 mg/m ³ (as Zr)	10 mg/m ³ (as Zr)	10 mg/m ³ (as Zr)	10 mg/m ³ (as Zr)	Not established
tin dioxide	TWA	2 mg/m ³ (as Sn)	2 mg/m ³ TD 2 mg/m ³	2 mg/m ³ (as Sn)	2 mg/m ³ (as Sn)	Not established
	STEL	Not established	Not established	Not established	4 mg/m ³ (as Sn)	Not established
Stoddard solvent	TWA	100 ppm	500 ppm	100 ppm	100 ppm	Not established
	STEL	Not established	Not established	Not established	200 ppm	Not established
Isopropyl alcohol	TWA	200 ppm	400 ppm	200 ppm	400 ppm	Not established

8 . Exposure controls/personal protection

	STEL	400 ppm	Not established	400 ppm	500 ppm	established Not established
carbon black respirable	TWA	3 mg/m ³	3.5 mg/m ³	3 mg/m ³	3.5 mg/m ³	Not established
	STEL	Not established	Not established	Not established	7 mg/m ³	Not established
aluminium hydroxide	TWA	1 mg/m ³ 1 mg/m ³ R	Not established	1 mg/m ³ R	Not established	Not established
2-butanone oxime	TWA	Not established	Not established	Not established	Not established	3 ppm
	STEL	Not established	Not established	Not established	Not established	10 ppm
crystalline silica respirable (<10 microns)	TWA	0.025 mg/m ³ R	10 MG/M3 / (%SiO ₂ +2) R Z 250 MPPCF / (%SiO ₂ +5) R Z	0.1 mg/m ³ R	0.1 mg/m ³ R	Not established
2-ethylhexanoic acid	TWA	5 mg/m ³	Not established	5 mg/m ³	Not established	Not established

Key to abbreviations

A	= Acceptable Maximum Peak	S	= Potential skin absorption
ACGIH	= American Conference of Governmental Industrial Hygienists.	SR	= Respiratory sensitization
C	= Ceiling Limit	SS	= Skin sensitization
F	= Fume	STEL	= Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	= Occupational Safety and Health Administration.	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes : Safety glasses with side shields.

8 . Exposure controls/personal protection

- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Respiratory** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: -6.11°C (21°F)
- Color** : Various
- Odor** : Not available.
- pH** : Not available.
- Boiling/condensation point** : >37.78°C (>100°F)
- Melting/freezing point** : Not available.
- Specific gravity** : 0.99
- Density (lbs / gal)** : 8.26
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Volatility** : 59% (v/v), 52% (w/w)
- Evaporation rate** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- % Solid. (w/w)** : 47.92

Physical property values shown in this section are calculated averages. For specific product information, contact your PPG Sales Representative.

10 . Stability and reactivity

- Stability** : The product may not be stable under certain conditions of storage or use.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid increased storage temperature. Pressure hazard
- Materials to avoid** : Reactive or incompatible with the following materials: water, acids, oxidizing materials, strong alkalis
- Hazardous decomposition products** : Formaldehyde.

10 . Stability and reactivity

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

11 . Toxicological information**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LD50 Oral	Rat	4.3 g/kg	-
	LD50 Dermal	Rabbit	>1.7 g/kg	-
	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
diiron trioxide	LD50 Oral	Rat	10 g/kg	-
	LD50 Oral	Rat	>10 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
titanium dioxide	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	4000 ppm	4 hours
	LD50 Oral	Rat	10.768 g/kg	-
ethylbenzene	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LC50 Inhalation Vapor	Rat	>21.1 mg/l	4 hours
	LD50 Oral	Rat	1.6 g/kg	-
n-butyl acetate	LD50 Dermal	Rabbit	10.206 g/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
	LC50 Inhalation Vapor	Rat	11243 ppm	4 hours
heptan-2-one	LD50 Oral	Rat	636 mg/kg	-
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m3	4 hours
butanone	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Dermal	Rabbit	>5 g/kg	-
	LC50 Inhalation Vapor	Rat	72600 mg/m3	4 hours
toluene	LD50 Oral	Rat	>20 g/kg	-
	LD50 Dermal	Rabbit	5.1 g/kg	-
	LC50 Inhalation Vapor	Rat	5.1 g/kg	-
2-methoxy-1-methylethyl acetate	LD50 Oral	Rat	>5 g/kg	-
	LD50 Dermal	Rabbit	4.396 g/kg	-
	LC50 Inhalation Vapor	Rabbit	12800 mg/kg	-
tin dioxide	LD50 Oral	Rat	12800 mg/kg	-
	LD50 Oral	Rat	72600 mg/m3	4 hours
	LD50 Oral	Rat	72600 mg/m3	4 hours
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	LD50 Oral	Rat	>5 g/kg	-
	LD50 Oral	Rat	4.396 g/kg	-
	LD50 Dermal	Rabbit	12800 mg/kg	-
Stoddard solvent	LD50 Oral	Rat	12800 mg/kg	-
	LD50 Oral	Rat	72600 mg/m3	4 hours
	LD50 Oral	Rat	72600 mg/m3	4 hours
Isopropyl alcohol	LD50 Oral	Rat	8400 mg/kg	-
	LD50 Dermal	Rabbit	3.48 g/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Solvent naphtha (petroleum), light aromatic	LD50 Oral	Rat	>15400 mg/kg	-
	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Oral	Rat	3.125 g/kg	-
polychloro copper phthalocyanine	LD50 Oral	Rat	>6 g/kg	-
	LD50 Oral	Rat	8500 mg/m3	4 hours
	LD50 Oral	Rat	8500 mg/m3	4 hours
carbon black respirable	LD50 Oral	Rat	2.33 g/kg	-
	LD50 Dermal	Rabbit	>10 g/kg	-
	LD50 Oral	Rat	>6700 mg/m3	4 hours
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	930 mg/kg	-
	LD50 Oral	Rat	200 uL/kg	-
	LD50 Dermal	Rabbit	200 uL/kg	-
Naphtha (petroleum), hydrotreated heavy	LD50 Oral	Rat	1600 mg/kg	-
	LD50 Oral	Rat	1600 mg/kg	-
	LD50 Dermal	Rabbit	1.26 g/kg	-
benzyl butyl phthalate	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Dermal	Rabbit	1.26 g/kg	-
2-butanone oxime	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Dermal	Rabbit	1.26 g/kg	-
2-ethylhexanoic acid	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Oral	Rat	1.26 g/kg	-
	LD50 Dermal	Rabbit	1.26 g/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

11 . Toxicological information

Conclusion/Summary : Not available.

Defatting irritant : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Target organs : Contains material which causes damage to the following organs: brain, central nervous system (CNS), eye, lens or cornea.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, liver, mucous membranes, heart, spleen, peripheral nervous system, gastrointestinal tract, cardiovascular system, upper respiratory tract, skin, ears, testes, thyroid.

Carcinogenicity

Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Classification

Product/ingredient name	ACGIH	IARC	NTP	OSHA
Xylene	A4	3	-	-
diiron trioxide	A4	3	-	-
titanium dioxide	A4	2B	-	-
ethylbenzene	A3	2B	-	-
Aluminium powder (stabilized)	A4	-	-	-
toluene	A4	3	-	-
Silica gel, pptd., cryst.-free	-	3	-	-
zirconium dioxide	A4	-	-	-
Isopropyl alcohol	A4	3	-	-
carbon black respirable	A3	-	-	-
aluminium hydroxide	A4	-	-	-
benzyl butyl phthalate	-	3	-	-
crystalline silica respirable (<10 microns)	A2	1	Known to be a human carcinogen.	-

Carcinogen Classification code: ACGIH: A1, A2, A3, A4, A5
IARC: 1, 2A, 2B, 3, 4
NTP: Proven, Possible
OSHA: +
Not listed or regulated as a carcinogen: -

Teratogenicity

Developmental effects : Contains material which may cause developmental abnormalities, based on animal data.

Fertility effects : Contains material which may impair male fertility, based on animal data. Contains material which may impair female fertility, based on animal data.

12 . Ecological information

Environmental effects : Water polluting material. May be harmful to the environment if released in large quantities.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Xylene	Acute LC50 3300 to 4093 ug/L Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss	96 hours
ethylbenzene	Acute LC50 4200 ug/L Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss	96 hours
	Acute LC50 5100 to 5700 ug/L Marine water	Fish - Atlantic silverside - Menidia menidia	96 hours

12 . Ecological information

	Acute EC50 2930 to 4400 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours	
	Chronic NOEC 3300 ug/L Marine water	Fish - Atlantic silverside - Menidia menidia	96 hours	
	Chronic NOEC 6800 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours	
n-butyl acetate	Acute LC50 18000 to 19000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours	
heptan-2-one	Acute LC50 131000 to 137000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours	
butanone	Acute LC50 3220000 to 3320000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours	
	Acute LC50 >400 ppm Marine water	Fish - Sheepshead minnow - Cyprinodon variegatus	96 hours	
	Acute LC50 >520000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours	
	Chronic NOEC 400 ppm Marine water	Fish - Sheepshead minnow - Cyprinodon variegatus	96 hours	
	Chronic NOEC <70000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours	
	toluene	Acute LC50 5800 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss	96 hours
		Acute EC50 6000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
Chronic NOEC 28000 ug/L Fresh water		Daphnia - Water flea - Daphnia magna	48 hours	
Isopropyl alcohol	Acute LC50 >1400000 ug/L	Fish - Bluegill - Lepomis macrochirus	96 hours	
benzyl butyl phthalate	Acute LC50 >780 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours	
	Acute LC50 >680 ug/L Fresh water	Fish - Sheepshead minnow - Cyprinodon variegatus	96 hours	
	Acute EC50 >0.76 mg/L Fresh water	Daphnia - Water flea - Daphnia magna	2 days	
	Chronic NOEC 360 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus	96 hours	
	Chronic NOEC 680 ug/L Fresh water	Fish - Sheepshead minnow - Cyprinodon variegatus	96 hours	
	Chronic NOEC 620 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours	
	2-butanone oxime	Acute LC50 843000 to 914000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours

12 . Ecological information

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	TDG	Mexico	IMDG
UN number	1263	1263	1263	1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3
Packing group	II	II	II	II
Environmental hazards	No.	Yes.	No.	Yes.
Marine pollutant substances	Not applicable.	(Solvent naphtha (petroleum), light aromatic, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)	Not applicable.	(benzyl butyl phthalate, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)
Product RQ (lbs)	53.161	Not applicable.	Not applicable.	Not applicable.
RQ substances	(xylene, ethylbenzene)	Not applicable.	Not applicable.	Not applicable.

Additional information

- DOT** : Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- TDG** : The marine pollutant mark is not required when transported by road or rail.
- Mexico** : None identified.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory information

- United States inventory (TSCA 8b)** : All components are listed or exempted.
- Australia inventory (AICS)** : Not determined.
- Canada inventory (DSL)** : All components are listed or exempted.
- China inventory (IECSC)** : Not determined.
- Europe inventory (REACH)** : Please contact your supplier for information on the inventory status of this material.
- Japan inventory (ENCS)** : Not determined.
- Korea inventory (KECI)** : At least one component is not listed.
- New Zealand (NZIoC)** : Not determined.
- Philippines inventory (PICCS)** : At least one component is not listed.

United States

SARA 302/304: No products were found.

CERCLA: Hazardous substances.: [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper: No RQ is being assigned to the generic or broad class.; [1-[[2-hydroxyphenyl]imino]methyl]-2-naphtholato(2-)-N,O,O']copper: No RQ is being assigned to the generic or broad class.; chromium (III) oxide: No RQ is being assigned to the generic or broad class.; benzyl butyl phthalate: 100 lbs. (45.4 kg); [1,3,8,16,18,24-hexabromo-2,4,9,10,11,15,17,22,23,25-decachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]copper: No RQ is being assigned to the generic or broad class.; copper chlorophthalocyanine: No RQ is being assigned to the generic or broad class.; polychloro copper phthalocyanine: No RQ is being assigned to the generic or broad class.; 29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper: No RQ is being assigned to the generic or broad class.; toluene: 1000 lbs. (454 kg); ammonium iron(3+) hexakis(cyano-C)ferrate(4-): No RQ is being assigned to the generic or broad class.; butanone: 5000 lbs. (2270 kg); n-butyl acetate: 5000 lbs. (2270 kg); ethylbenzene: 1000 lbs. (454 kg); xylene: 100 lbs. (45.4 kg);

SARA 311/312 SDS Distribution - Chemical Inventory - Hazard Identification:

<u>Chemical name</u>	<u>CAS #</u>	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Reactive</u>	<u>Pressure</u>
xylene	1330-20-7	Y	N	Y	N	N
diiron trioxide	1309-37-1	N	N	N	N	N
titanium dioxide	13463-67-7	N	Y	N	N	N
Mica-group minerals	12001-26-2	N	N	N	N	N
ethylbenzene	100-41-4	Y	Y	Y	N	N
n-butyl acetate	123-86-4	Y	N	Y	N	N
Naphtha (petroleum), heavy alkylate	64741-65-7	Y	N	Y	N	N
heptan-2-one	110-43-0	Y	N	Y	N	N
Talc , not containing asbestiform fibres	14807-96-6	Y	N	N	N	N
Aluminium powder (stabilized)	7429-90-5	N	N	N	Y	N
butanone	78-93-3	Y	N	Y	N	N
ammonium iron(3+) hexakis(cyano-C)ferrate(4-)	25869-00-5	N	N	N	Y	N
toluene	108-88-3	Y	Y	Y	N	N
Silica gel, pptd., cryst.-free	112926-00-8	N	N	N	N	N
2-methoxy-1-methylethyl acetate	108-65-6	Y	N	Y	N	N
zirconium dioxide	1314-23-4	N	N	N	N	N
tin dioxide	18282-10-5	N	N	N	N	N
Stoddard solvent	8052-41-3	Y	N	Y	N	N
Isopropyl alcohol	67-63-0	Y	N	Y	N	N
Solvent naphtha (petroleum), light aromatic	64742-95-6	Y	N	Y	N	N
[1,3,8,16,18,24-hexabromo-2,4,9,10,11,15,17,22,23,25-decachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]copper	14302-13-7	Y	N	N	N	N
carbon black respirable	1333-86-4	N	Y	N	N	N
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	Y	N	N	N	N

15. Regulatory information

quino[2,3-b]acridine-6,7,13,14(5H, 12H)-tetrone	1503-48-6	Y	N	N	N	N
Resin acids and Rosin acids, calcium salts	9007-13-0	Y	N	N	N	N
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Y	N	Y	N	N
aluminium hydroxide	21645-51-2	N	N	N	N	N
benzyl butyl phthalate	85-68-7	Y	Y	N	N	N
2-butanone oxime	96-29-7	Y	Y	Y	Y	N
crystalline silica respirable (<10 microns)	14808-60-7	N	Y	N	N	N
2-ethylhexanoic acid	149-57-5	Y	Y	N	N	N
Product as-supplied :		Y	Y	Y	Y	N

SARA 313

Supplier notification

Chemical name

CAS number

Concentration

xylene	1330-20-7	60 - 100
ethylbenzene	100-41-4	15 - 40
Aluminium powder (stabilized)	7429-90-5	7 - 13
toluene	108-88-3	5 - 10
Isopropyl alcohol	67-63-0	1 - 5
[1,3,8,16,18,24-hexabromo-2,4,9,10,11,15,17,22, 23,25-decachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]copper	14302-13-7	1 - 5

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada

WHMIS (Canada)

Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

Mexico

Classification

Flammability : 3 Health : 2 Reactivity : 1

16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * Flammability : 3 Physical hazards : 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 2 Flammability : 3 Instability : 1

Date of previous issue : 2/5/2014.

Organization that prepared the MSDS : EHS

16 . Other information

✔ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.